

House Kit

Radon and indoor air quality system Multi-room connected monitoring

DOWNLOADS





The Airthings House Kit has everything you need to start monitoring the quality of your air, for a healthier home. This multi-room kit includes: Wave, the very first smart radon detector, Wave Mini, for mold risk indication, airborne chemicals, humidity and temperature, and Hub, which brings everything online. Simply connect the Hub to the internet and set up the monitors using the Airthings Wave App. You then gain visibility into indoor air contaminants in multiple rooms in your home, no matter where you are. Data is available via the free Airthings Wave app (iOS/Android) as well as online with the Airthings Dashboard with more advanced analytics options.

COMPLETE HEALTH

Continuous monitoring of radon is necessary to minimize potential health risks. Compare data and find trends using the Airthings App and online dashboard. When you know what's in your air, small changes to your daily habits make a big difference to your family's health. Users have complete access to long and short term data as well as tips to reduce indoor air hazards, optimize ventilation and save energy.

WAVE MINI: MOLD RISK INDICATION

When you see mold, it's too late. We have created an algorithm based on the ASHRAE mold index using our humidity and temp sensors to show mold growth risk before the problem actually occurs. Placement is key, so please see our mold page for more details. airthings.com/mold-risk-indicator

HOUSE KIT SPECIFICATIONS & ADDITIONAL INFORMATION

Bluetooth is used for setup of Hub, Wave 2nd Gen and Wave Mini. Bluetooth frequency band: 2402 - 2480 MHz SmartLink wireless protocol is used between Hub, Wave 2nd Gen and Wave Mini SmartLink frequency band in Europe: 868 - 870 MHz SmartLink frequency band in North America: 902 - 928 MHz

PACKAGE CONTENT

Wave 2nd Gen Wave Mini Hub Regulatory Information

PACKAGE

Weight: 1250g, 44oz Dimensions: 205x130x165mm (See devices for individual sizes of each)

INTEGRATIONS

The Hub brings your Airthings products online, wirelessly. Live data allows for full integration into your smart home: set alerts, receive air quality measurements, give voice commands, connect to a smart plug or smart product to control your thermostat, air purifier, or humidifier—the options are endless.



REQUIREMENTS

Ethernet connection for Hub One of the 3 latest major versions of iOS or Android supporting Bluetooth 4.2 or later Bluetooth 4.2 or later to set up your Hub, Wave 2nd Gen and Wave Mini

PRODUCT CODES

EAN: 7090031104207 UPC: 854232008156 SKU: 420 Device serial number: 4200xxxxx











WAVE RADON

PRODUCT FEATURES

Sensors: Radon, Temp & Humidity Visual indicator: Red/Yellow/Green glow ring Long battery life:~24 months Supports wall or ceiling mount Free mobile app for iOS and Android Web dashboard Mobile notifications

IAQ SENSOR SPECIFICATIONS

Sensor sampling interval: 5 minutes Sensor Resolution: Temperature \mp 0.1°C/F Humidity ∓1%

ADDITIONAL INFORMATION

PACKAGE CONTENT

Air Quality Detector 2 AA alkaline batteries Instruction Manual Mounting screw

DEVICE Weight: 216g, 7.6oz Dimensions: 120x36mm, 4.7x1.4in

WAVE MINI

FUNCTIONS

Sensors: Mold risk indicator, VOC, Temperature and Humidity Visual feedback: Red/Yellow/Green glow indicator Long battery life: > 3 years* Supports wall mounting or table stand Free mobile app for iOS and Android Free online dashboard Mobile and web notifications

ADDITIONAL INFORMATION

PACKAGE CONTENT

Air Quality Detector 3 x AA alkaline batteries Instruction Manual Table stand

DEVICE

Weight: 135g, 4.8oz Dimensions: 80x26mm, 3.14x1in

ADDITIONAL SPECIFICATIONS

Operational Environment: 4°C to 40°C, 39°F to 104°F Power: 2 AA alkaline batteries

RADON SPECIFICATIONS

Radon sampling: Passive diffusion chamber Detection method: Alpha spectrometry Measurement range: 0 – 20,000 Bq/m³/ 500 pCi/L Accuracy/precision at 200 Bq/m³ / 5.4 pCi/L: After 7 days ~ 10 % After 2 months ~ 5 %

PRODUCT CODES

NOT FOR INDIVIDUAL SALE MODEL: 2950 Serial Number : 2950 xxxxx

SPECIFICATIONS

Sensor sampling interval: 5 minutes Sensor Resolution / Accuracy: Temperature: 0.1 / ±1 °C/F Humidity: 1 / ±3 % Settling time: TVOC ~7 days Operational Environment: 4°C to 40°C, 39°F to 104°F Power: 3 x AA alkaline batteries Wireless: Bluetooth & SmartLink

PRODUCT CODES

NOT FOR INDIVIDUAL SALE MODEL: 2920 Device serial number: 2920xxxxx

HUB

HUB PRODUCT FEATURES

Remote access to Airthings devices : Wave 2nd gen (device serial number 2950xxxxx) Wave Plus (device serial number 2930xxxxx) Wave Mini (device serial number 2920xxxxx)

One Hub can connect to up to 10 Airthings devices Long-range wireless connection with Airthings SmartLink

Live data streaming to the cloud

Free mobile app for iOS and Android

- Mounting options: Freestanding or mounted
- LED status indicators: Power, cloud and SmartLink connection

HUB SPECIFICATIONS

Operational Environment: 4° - 40°C, 39° - 104°C Power supply: 100–240 V AC / 50–60Hz Protocols: Airthings SmartLink Estimated range: Easily covers most residential homes Connection: Ethernet port





туос



TEMP



ADDITIONAL INFORMATION

HUB PACKAGE CONTENT Airthings Hub Ethernet cable Instruction Manual Mounting bracket Rubber bumper pads Power supply adaptor US interchangeable supply blade EU interchangeable supply blade UK interchangeable supply blade

DEVICE

Weight: 249g, 8.8 oz Dimensions: 125x125x25mm, 4.9x4.9x1 in

PRODUCT CODES

NOT FOR INDIVIDUAL SALE MODEL: 2810 Device serial number: 2810xxxxxx





MOLD



